PSC 250T ECE ELASTIC

Unique modern thermal insulation material.



AGAINST FUNGI AND MOSS!





- Prevents condensation. Roof does not overheat and does not freeze.
- ✓ Very suitable as a substrate for PV panels! For all types of roofing.
- ✓ Simple and quick application. The layers is only 1 mm!



Březník 218, CZ - 675 74 Březník Phone: +420 602 690 695 E-mail: info@psctherm.cz, www.psctherm.cz

PSC 250T ECE ELASTIC

Unique modern thermal insulation material.


✓ INSULATING AND PROTECTIVE COATING

EXTENDS THE LIFE OF THE ROOF

RESISTANT TO DIRT

Highly effective, decorative coating for use on roofing materials or other building and construction elements made of PVC, PC, PS, asphalt shingles (IPA), plastics, polycarbonate, hardened PVC, etc.

Resists weathering, acid rain and other standard weathering



- Consumption of PSC 250T ECE Elastic: 0,8 litres / 1 square metre
- Application temperaturee: from 8 degrees Celsius
- Drying time: up to 24 hours depending on temeperature and nature of the environment

Always use PSC 250T ECB BASIC B primer.

This product can also be ordered in a version COLOR. Different colours can be applied shades in the RAL range.







PSC ELASTIC

PLASTIC / PVC / ASPHALT



Březník 218, CZ - 675 74 Březník Phone: +420 602 690 695

E-mail: info@psctherm.cz, www.psctherm.cz